# AVZ-H610

Display - Dual display supported

## Specification

| Spec Item | | Description |
|---|---|---|
| Form factor | SBC Form Factor | CPUIntel® Core? i5-2xxT (above 2.7 GHz)Intel® Core? i3-2xxT (above 2.5 GHz)Intel® Pentium® G6xxT (above 2.2 GHz)Chipse: Intel® H61System Memory:On-board DDR3 2 GB memory1 x 204-pin DDR3 SO-DIMM (system max: 10 GB) |
| System | Cooling method / System Fan | Fanless |
| | Drive Bays | 1 x 2.5' SATA 3Gb/s HDD/SSD bay |
| I/O Interface | I/O Ports | 2 x USB 3.04 x USB 2.0Ethernet:2 x RJ-45PCIe GbE by Realtek 8111ECOM Port:4 x RS-232 (DB-9, two with isolation)2 x RS-422/485 (RJ-45)Digital I/O:8-bit digital I/O, 4-bit input/4-bit outputDisplay:1 x VGA, 1 x DVI-IResolution:VGA: Up to 2048 x 1536@75HzDVI-I: Up to 1920 x 1080@60Hz |
| Environment | Operating Temperature | -20°C ~ 60°C with air flow (SSD) |
| | Humidity | 5% ~ 95%, non-condensing |
| Dimensions | Dimensions | 133 x 269 x 208 |
| Weight | Weight | 4.2 kg/6.3 kg |
| Color | Color | Black C + Silver |
| Expansion Slots | Expansion Slots | PCI:2P1E: 2 x PCI, 1P2E: 1 x PCIPCLe:2P1E: One PCIe x8 (physical PCIe x16 slot)1P2E: One PCIe x1 (physical x4 slot),One PCIe x8 (physical x16 slot) |