



AVZ-N406

4U Compact chassis

Specification

| Specifications | |
|-------------------------------------|--|
| Dimension (W*H*D) | 19 ?x 7? x 17.72?/ 482 x 177 x 450mm |
| Material Construction | Heavy-duty High-end cold-rolled steel Thickness:1.0 |
| M/B Size | CEB (12"x10.5") |
| Expansion | 7 slots rear side ATX or 14slot |
| Control & Indicator | 1x Power switch +1x Reset switch 1 x LED (power) +1 x LED (HDD), 1 x LED (KB-LK) 2 x 2.0 USB |
| Cooling Fans | 1x 12cm Fan in front+2 x 6cm at rear or topcover (option) |
| DriveBay | 2 x 5.25? + 1 x 3.5? (external) + 8 x 3.5? (internal) |
| Power Supply | Standard PS-2 ATX or PS-2 size Mini-Redundant Power supply 300w~500w |
| Sliding rail | 20" ball bearing sliding rail (option) |
| Color | Black or Beige |
| Operation Temperature | Up to 50C (122?) |
| Operation Humidity (Non-condensing) | Up to 90% |
| Packing Measurement CBF / CBM | 2.6 / 0.07 |
| Packing N.W / G.W | 10.2KGS /12.1KGS |
| | |